HDA

TRIVELLA IDRAULICA
Hydraulic auger



ARTICOLO Item	ESCAVATORE Excavator (t)	PORTATA D'OLIO Oil flow rate (l/min)	PRESSIONE MAX Max pressure (bar)	COPPIA MAX Max torque (Nm)	ALBERO ESAGONALE Hex shaft (mm)	PESO Weight (kg)	CODICE Code	PREZZO Price
HDA 1	1,5 – 3	60	200	1800	50	50	1.322.01.001	
HDA 2	3 – 5,5	75	200	3000	50	65	1.321.01.001	
HDA 3	6 – 8	75	240	4000	50	95	1.304.01.250	
HDA 4	8 – 11	125	240	4700	70	150	1.307.01.200	
HDA 5	10 – 14	150	350	8000	70	180	1.308.01.250	







ACCESSORI / Accessories

ARTICOLO / Item	SUPPORTO PER TRIVELLE HDA 1 / 2 / 3 Double pin cradle HDA 1 / 2 / 3
CODICE / Code	2.320.10.001
PREZZO / Price	

Potenza e affidabilità per trivellazioni profonde

- Ideale per costruire recinzioni, palizzate, impianti agricoli, pozzi.
- Raggiunge profondità di diversi metri con l'utilizzo di prolunghe ad asta elicoidale.
- Struttura resistente a protezione del riduttore.
- Moto-riduttori epicicloidali di fabbricazione italiana, con elevata potenza in uscita.
- Albero attacco chiave esagonale 50 mm / 70 mm.
- Punte disponibili da Ø 100 a 500 mm per terreni normali o rocciosi.

Power and reliability for deep drilling

- Ideal for building fences, palisades, agricultural systems, wells.
- Helical rod extensions can reach depths of several meters.
- Sturdy structure protecting the gear motor.
- Italian-made planetary gear motors with high output power.
- Hexagonal drive shaft: 50 mm / 70 mm.
- Available drill bits from Ø 100 to 500 mm for normal or rocky soils.