



An equipment for everybody.

Tractor buckets

- Solid structure – max load 2500 kg
- Tractor linkage 1 + 2 + 3 category,
- Terminal blade in wear resistant steel
- Rear mobile closing



The employment in all situations.

The tractor bucket is one of the more common and used equipment. Now, with our HFS PBE buckets we can offer an equipment that will help you in the collection and in the transport of every kind of material, but it is not all. Our solid bucket structure in fact will permits you to push with your tractor to level terrains and to set roads, farming and woodland routes, to load rocks, ground and other materials in an easy and fast way.

Our innovative overturning system with a central cylinder and mechanical connecting rod is solid and reliable because the cylinder is in the most protected position and guarantees the most possible overturning (86 degrees of inclination) in a small time because the connecting rod multiplies the movement in relation to the cylinder advancement. These characteristics are the proof of the unicity of our product and of the attention we put when we produce all our equipment, on the tractor buckets as well for example, to make them special for you.





MODEL	JOINTS CATEGORY	L (CM)	W (CM)	H (CM)	WEIGHT (KG)	VOLUME WITHOUT BANK (L)	VOLUME WITH OPEN BANK (L)	LOAD (KG)	BANK WEIGHT (KG)	TOTAL WEIGHT (KG)
HFS PBE 140/80	I / II	140	80	50	290	560	620	1500	22	312
HFS PBE 160/80	I / II	160	80	50	310	640	710	1500	23	333
HFS PBE 180/80	I / II	180	80	50	330	720	800	1500	24	354
HFS PBE 200/80	I / II	200	80	50	350	800	890	1500	25	375
HFS PBE 180/100	II / III	180	100	50	350	900	890	2000	24	374
HFS PBE 200/100	II / III	200	100	50	400	1000	1100	2000	26	426
HFS PBE 220/100	II / III	220	100	50	450	1100	1210	2000	28	478
HFS PBE 240/100	II / III	240	100	50	530	1200	1320	2500	30	560

