

PINZE PER TRONCHI

Soluzioni robuste e versatili per escavatori e gru




- Pinze per tronchi adatte a caricatori forestali, gru ed escavatori.
- Costruite con materiali di alta qualità.
- Perni in 39NiCrMo3 e boccole con bronzine.
- Ottima geometria per la presa e il rilascio dei tronchi.
- Elevata forza di chiusura.
- Disponibili anche senza pale sulle forche.
- Possibilità di installare un kit motosega.
- Progettate per afferrare, sollevare e caricare grandi quantità di tronchi in sicurezza.
- Disponibili con forche chiuse o solo punte (modelli SP).

- Log grapples suitable for forestry loaders, cranes, and excavators.
- Built with high-quality materials.
- Pins made from 39NiCrMo3 and bushings with bronze liners.
- Excellent geometry for gripping and releasing logs.
- High closing force.
- Also available without blades on the forks.
- Option to install a chainsaw kit.
- Designed to securely grasp, lift and load large quantities of logs.
- Grapples arms with or without terminal plates (SP models).

LOG GRAPPLES

Durable and versatile solutions for excavators and cranes





	Peso escavatore <i>Excavatore weight</i>	Peso <i>Weight</i>	Superficie <i>Surface</i>	Pressione <i>Pressure</i>	Portata <i>Capacity</i>	A	B	C	D	E	L
HLG F8	1.5 – 2.5 t	65 kg	0.12 m ²	max 200 bar	500 kg	70 mm	410 mm	550 mm	1090 mm	650 mm	330 mm
HLG F10	2 – 3 t	85 kg	0.19 m ²	max 200 bar	1900 kg	80 mm	440 mm	575 mm	1180 mm	695 mm	395 mm
HLG F15 *	3 – 4.5 t	118 kg	0.23 m ²	max 200 bar	2100 kg	75 mm	495 mm	675 mm	1400 mm	790 mm	425 mm
HLG F15S *	4.5 – 6 t	131 kg	0.23 m ²	max 200 bar	2100 kg	75 mm	495 mm	675 mm	1400 mm	850 mm	450 mm
HLG F25 *	6 – 8 t	196 kg	0.27 m ²	max 200 bar	3100 kg	95 mm	580 mm	675 mm	1610 mm	985 mm	490 mm
HLG F 35	7.5 – 9 t	265 kg	0.38 m ²	max 200 bar	3500 kg	120 mm	630 mm	890 mm	1740 mm	985 mm	500 mm
HLG S40 *	8 – 11 t	265 kg	0.31 m ²	max 230 bar	4000 kg	100 mm	590 mm	905 mm	1650 mm	935 mm	470 mm
HLG S40H *	9 – 12 t	300 kg	0.31 m ²	max 230 bar	4000 kg	100 mm	590 mm	905 mm	1650 mm	935 mm	500 mm
SUPER 1800 *	12 – 16 t	440 kg	0.40 m ²	max 250 bar	7000 kg	120 mm	680 mm	980 mm	1820 mm	1005 mm	630 mm
SUPER 2000	12 – 16 t	505 kg	0.48 m ²	max 250 bar	7000 kg	150 mm	730 mm	1010 mm	2010 mm	1100 mm	630 mm

Versione SP - forche senza piastre terminali / SP version: grapple arms without terminal plates



	Peso escavatore <i>Excavatore weight</i>	Peso <i>Weight</i>	Superficie <i>Surface</i>	Pressione <i>Pressure</i>	Portata <i>Capacity</i>	A	B	C	D	E	L
HLG F10 SP	2 – 3 t	100 kg	0.19 m ²	max 200 bar	1900 kg	80 mm	440 mm	575 mm	1180 mm	695 mm	425 mm
HLG F15 SP *	4.5 – 6 t	140 kg	0.23 m ²	max 200 bar	2100 kg	75 mm	495 mm	675 mm	1400 mm	850 mm	450 mm
HLG F25 SP *	6 – 8 t	225 kg	0.27 m ²	max 200 bar	3100 kg	95 mm	580 mm	675 mm	1610 mm	985 mm	530 mm
HLG F35 SP	7.5 – 9 t	305 kg	0.38 m ²	max 200 bar	3500 kg	120 mm	630 mm	890 mm	1740 mm	985 mm	530 mm
HLG S40 SP *	8 – 11 t	300 kg	0.31 m ²	max 230 bar	4000 kg	100 mm	590 mm	905 mm	1650 mm	935 mm	530 mm
SUPER 1800 SP *	12 – 16 t	430 kg	0.40 m ²	max 250 bar	7000 kg	120 mm	680 mm	980 mm	1820 mm	1005 mm	630 mm
SUPER 2000 SP	12 – 16 t	495 kg	0.48 m ²	max 250 bar	7000 kg	150 mm	730 mm	1010 mm	2010 mm	1100 mm	630 mm

