HTR

BARRA TRONCARAMI
Branch cutter bar







ARTICOLO Item	LUNGH. TAGLIO Cut length (mm)	Ø MAX Max Ø (mm)	PORTATA OLIO Oil flow rate (l/min)	PRESSIONE MAX Max pressure (bar)	FREQUENZA DI TAGLIO Cutting frequency (cuts/min)	PESO Weight (kg)	ESCAV. Excav. (t)	CODICE Code	PREZZO Price
HTR 5/150	1500	50	60	250	200	195	4 - 6	1.825.05.150	
HTR 10/150	1580	100	60	250	84	230	5 - 8	1.825.10.150	
HTR 15/160	1600	150	60	250	84	260	6 - 12	1.825.15.160	

SELLE DI AGGANCIO A PERNI / Mounting hitch with pins

	HTR 5/150	HTR 10/150		HTR 15 /160		
ESCAVATORE Excavator (t)	4 - 6	5 - 6	6 - 8	6 - 8	8 - 10	10 - 12
PREZZO Price						

- Velocità di taglio fino a 200 battiti/min.
- Taglio netto e veloce, fino a 15cm di diametro.
- Snodo orientabile a 360°.
- Lame in acciaio speciale HB 450, durata pressoché infinita.
- Barre anti-usura in ottone.
- Fresatura speciale per un taglio preciso senza danni alla pianta.
- Valvola regolatrice di flusso: compatibile con qualsiasi escavatore, decespugliatore o potatore.
- Tecnologia anti-shock: protegge macchina e ostacoli in caso di urto.
- Robusta, versatile e con una manutenzione ridotta al minimo.

- Cutting speed up to 200 strokes/min.
- Clean and fast cut, up to 15 cm (6”) in diameter.
- 360° swivel joint.
- Blades made of HB 450 special steel for virtually infinite lifespan.
- Brass wear plates.
- Special milling for precise cutting without damaging the plant.
- Flow control valve: compatible with any excavator, brush cutter, or pruner.
- Anti-shock technology: protects the machine and obstacles in case of impact.
- Heavy-duty, versatile, and requires minimal maintenance.